

Hasflex PAK Semi-Rigid Aluminium Flexible Ducting



Hasflex PAK Semi-Rigid Aluminium Flexible Ducting

Description

Non-Insulated Heavy-Duty aluminium semi rigid flexible duct reinforced with bronze coated bead wire.

Construction

Single layer product made of aluminium, formed into a semi rigid round flexible duct reinforced by a bronze coated bead wire helix.

Components

- 1 layer of 70-micron aluminium
- Bronze coated bead wire
- Water based adhesive in aluminium overlap

Specifications

- Wire pitch – 33mm for all sizes
- Duct diameters 80mm – 152mm:- wire diameter 0.9mm
- Duct diameters 200mm – 254mm:- wire diameter 1.1mm
- Duct diameters 356mm – 400mm:- wire diameter 1.3mm

Properties

- Fire – Tested UL181 – zero flame spread, zero smoke development
- Operating temperature is -30 degree C to +250 degree C
- Maximum air velocity 30m/s
- Maximum working pressure: +3000PA
- Maintains shape when extended

Available Diameters

- 80mm – 400mm
- Also available Insulated

Standard length

- 3Mtr Lengths



Head Office Heath Mill Road, Wombourne, Wolverhampton, West Midlands WV5 8AP

Head Office 01902 895161
Wolverhampton Branch 01902 895161
Hailsham Branch 01323 847910
London Branch 020 8803 9622

Rochester Branch 01634 672730
Stoke Branch 01782 274000
Bury Branch 0161 796 8226
Nottingham Branch 0115 979 4527

Eastleigh Branch 02380 612954
Liverpool Branch 01519 228933
Leeds Branch 01132 341971

sales@has-vent.co.uk www.has-vent.co.uk

Every effort is made to ensure that the information contained in HAS-Vent's literature is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company has a policy of continuous product development and reserves the right to alter, at any time, specifications, without prior notice.